

Table drilling machine

Stock number: 2004-42040

Type of machinery: Table drilling machine

Manufacturer:

Type:

Year: *

Control unit: conventional

Maker of control unit:

Country of origin:

Item location:

Delivery time:

Freight basis:



K-FDM

Seller



Von Profis für Profis
KIRCHNER

Kirchner GmbH
 Nikolaus-Fey-Str. 17
 97447 Gerolzhofen

Phone: 09382 9791 0

Fax: 09382 9791 79

E-Mail:

info@kirchner-holzbearbeitung.de

kirchner-holzbearbeitung.de

Description

230V / 1Ph

No. 3003010SET

Bench drill with V-belt drive in a new design

Easy to use safety switch according to IP 54 with undervoltage release and separate

Emergency stop impact switch Drilling depth stop

Precision machined, stable drill table with diagonal

extending T-slots and circumferential cooling water channel

Height adjustment of the drilling table via rack

Drill table inclinable by 45 ° and 360 ° rotatable

V-belt cover with safety switch

Aluminum die-cast quill lever in one piece

with softgrip handles

industrial engine

Precision Spindle bore

Machine operation including safety electronics

in 24 V DC

Table drilling machine

Heavy version of the entire machine

Room amenities:

Digital speed display and digital drilling depth display

Integrated in the housing

belt drive

Smooth running thanks to ground multi-tooth driver

Technical specifications:

Length (product) approx. 565 mm

Width / depth (product) approx. 275 mm

Height (product) approx. 840 mm

Weight (net) approx. 41.5 kg

Power drive motor 0.5 kW

Electrical voltage 230V

Phase (s) 1 Ph

Current type ~

Mains frequency 50 Hz

Column diameter 60 mm

Drilling capacity steel (S235JR) 16 mm

Continuous drilling capacity steel (S235JR) 12 mm

Quill stroke 65 mm

Spindle mount MK2

Projection 152 mm

Speed ??range 500 - 2520 min-1

Number of speed ranges 5

Drilling table working surface length 235 mm

Drilling table working surface width 220 mm

Drill table T-slots size 12 mm

Drill rotation 360 degrees

Drill bit pitch 45 degrees

Table drilling machine

Spindle distance - Drilling table max. 325 mm

Distance spindle - machine foot max. 530 mm

Machine foot working surface length 220 mm

Machine foot working surface width 230 mm

Machine foot T-slots size 16 mm

Machine foot T-slots number 2

Machine foot T-slots spaced 148 mm